

## QDX Series Stainless Steel Water Pump, Stainless Steel Impeller Submersible Pump For Garden Use And Home Dewatering



### Product Data

MODEL	POWER		FLOW (m <sup>3</sup> /h)	HEAD (m)	OUTLET (in)	GW (kg)	PACKING DMENSION (mm)
	KW	HP					
QDX5-10-0.37B	0.37	0.5	5	10	1.5"	10	170×240×390
QDX10-10-0.55B	0.55	0.75	10	10	1.5"	12	170×240×390
QDX15-10-0.75B	0.75	1	15	10	1.5"	14	170×240×390
QDX6-16-0.75B	0.75	1	6	16	1.5"	14	170×240×390
QDX25-7-1.1B	1.1	1.5	25	7	2"	16	170×240×390
QDX30-9-1.5B	1.5	2	30	9	2"	19	170×240×390
QDX35-12-2.2B	2.2	3	35	12	3"	21	210×250×460

### Specification

Power Cable: Standard cable is 10m;  
 Liquid Temperature: 104F(40°C) continuous;  
 Motor: B insulation class;  
 IP68 protection;  
 Single Phase: Built in thermal protector;  
 Accessories: Float switch is available.

### Part Specification

O-ring: Buna-N;  
 Motor Housing: 304 S.S;  
 Shaft: 304 S.S welding shaft;  
 Double-sided Mechanical Seal: Buna-N elastomers ;  
 Motor side: Carbon VS silicon Carbide;  
 Pump side: Silicon Carbide VS Silicon Carbide;  
 Impeller: 304 S.S welding;  
 Pump Casing: 304 S.S;  
 Shredding ring: Cast steel;  
 Grinding ring: Cast steel.

### Pump Installation And Features

Quickly and efficiently drain pools, ponds and flooded basement.  
 Float switch control the pump on and off automatically.  
 High-quality bearing, seals and stainless motor shaft with special treatment ensure long life .  
 Low consumption electric motor with overload protection ensure safe operation.